

IPX 80 - Voice and Video IPBX System

IPX 80 series is a Hybrid IPBX Server which supports both Voice and Video calls. It combines the reliability of PSTN and the cost effectiveness of VoIP to maximize on efficiency and savings.



Robust Hybrid Platform - Supports PSTN & VoIP (SIP / IAX Trunks).
Integrates PSTN lines and Analog extensions via plug in FXO/ FXS modules.
Best of both the worlds the reliability of PSTN & the cost effectiveness of VoIP.
Investment Protection - modular system supports Software upgrades.
Saves on Cabling costs - can be installed on existing Data network cabling.
Integrated Voicemail - over 3000 minutes Voicemail recording capability.
Customizable Auto attendant, Voicemail and IVR greeting messages.
Unified Messaging - records and forwards voicemail messages to email inbox.
Supports 30 to 80 concurrent calls and 100 to 1000 IP Extensions.
Supports BLF, DISA, Call Recording, Follow Me, Paging, VPN, Skype, CDR etc.

Supports - IP Video Phones, IP Doorstations, Wi-Fi Phones, iPhone, Android devices etc.

IPX 80 - Voice and Video IPBX System

IPX 802 - 1 FXO + 1 FXS port and 30 extensions, **IPX 804** - upto 4 FXS / FXO ports and 100 extensions , **IPX 808** - upto 8 FXS / FXO ports and 100 extensions, **IPX 816** - upto 16 FXS / FXO ports, 80 Concurrent calls and 1000 SIP Extensions.

30 Concurrent calls.

Direct Inward Dialing for SIP and IAX trunks.

Skype for SIP Trunk support.

Call Recording.

Direct Inward Station Access.

Call Hold, Transfer, Forwarding.

Call Parking and Pickup.

Paging and Intercom.

Caller ID, Phonebook.

Customizable Music on hold.

Flexible Dial Plan.

Multiple Ring Groups.

Busy Lamp Field support.

Conferencing.

Follow Me.

Three way calling.

T.38 Fax pass-through.

Integrated Voicemail.

Message waiting support.

Auto Attendant.

Customizable IVR system.

System Backup and Restore .

Echo Cancellation.

VPN and DDNS Support.

Barge in and whisper.

Call Queuing.

Call Data Logs.

Supports Static/ DHCP/ PPPOE.

Do not Disturb.

Automatic Route Selection.

Call Restriction.

Remote extension support.

Blacklist.

Web based configuration and Management.

Audio Codec's : G711Ulaw and Alaw, G726, G729, GSM, SPEEX.

Video Codec's : H.261, H.263, H.263+, H.264.

Hardware : 32 bit embedded RISC DSP, 1 G Onboard Nand Flash, 128M SDRAM.

Operating temperature: -10° to 45°C, Storage temperature: -30° to 65°C, Humidity: 10-80% non condensing, Power: AC 100-240V, Gross unit weight 1.73kg.