

# IPBX SOHO - Embedded PBX Server

IPBX Soho is a all in one Telephone System designed for Home Offices. It combines the reliability of PSTN and the cost effectiveness of VoIP into one single unit and offers the option to use both VoIP and PSTN lines to maximize efficiency and savings.



**Hybrid Platform - Supports PSTN and VoIP ( SIP Trunks).**

**Integrates PSTN lines and Analog extensions via plug in FXO/ FXS modules.**

The best of both the worlds the reliability of PSTN & the cost effectiveness of VoIP.

Investment Protection modular system supports Hardware & Software upgrades.

Save on Cabling costs – can be installed on existing Telephone / Data cabling.

Integrated Voicemail - over 2000 minutes Voicemail recording capability.

Customizable Auto attendant, Voicemail and IVR greeting messages .

Unified Messaging - forwards voicemail messages to your email inbox.

Supports 8 concurrent calls and 32 IP Extensions.

BLF updates, Queuing DISA , Call Recording, Follow Me, Ring Group, CDR etc.

# IPBX SOHO - Embedded PBX Server

Automated Attendant	Call Recording
Call Detail Records (CDR)	Blind and Attended Transfer
Conference Call	Dial Plan
Do Not Disturb (DND)	Three way Calling
Interactive Voice Response (IVR )	BLF Status Updates
Direct Inward Station Access (DISA)	Remote Extension
Music on Hold / Transfer	Toll Restriction
Ring Groups	Automatic Route Selection
Call Forwarding (Busy, No answer)	Distinctive Ringtones
Call Parking , Call Pickup	Paging and Intercom .
Blacklist, Firewall	Call routing
Route By Caller ID	Echo cancellation
Auto Provisioning	Toll restriction
Voicemail –4000 minutes flash memory	Music on Hold / Transfer
Caller ID Support	Message Waiting Support
Follow me	Automatic Route Selection
Skype Integration	Configuration backup and restore
Call Queuing	Web based software upgrade

**Specifications** - Supports upto 4 FXO / PSTN Lines, upto 4 FXS / Analog extensions, 8 concurrent calls, 32 SIP & 4 Analog extensions.  
Protocols : SIP (RFC 3261), T.38\*, DTMF: RFC 2833, SIP info, In-band. Codec : G711A /u-law, G726, G729,GSM, Speex,H 261, H263, H263p,H264, MPEG4.

**Physical Interface** - 1 x RJ 45 Ethernet interface Port, 4 x RJ11 Interface ports, Size : 193 x 153 x 30 mm, Weight : 500g., Power : 12V. 5 A, Operation Range : 0° - 50° C, Humidity 10-90% non condensing.