

2/3/4/5 Megapixel H.265 Remote Focus&Zoom Mini Bullet Network Camera



IP67

Motorized Lens

MS-C2963-F(I)PB/MS-C3763-F(I)PB/MS-C4463-F(I)PB/MS-C5363-F(I)PB

DATASHEET

KEY FEATURES

- ▶ **H.265+** (70~80% reduction in bandwidth, storage and bit rate compared with H.264.)
- ▶ **Powerful IR LEDs** (Equipped with 3rd generation dot matrix IR LEDs, guaranteeing excellent image quality, long lifespan and energy efficiency.)
- ▶ **Advanced Functions** (Boasting to support various advanced functions such as HLC, Defog, ROI.)
- ▶ **128G** (Supporting ultra-large external microSD/SDHC/SDXC card storage up to 128G.)
- ▶ **Adjustable 3-Axis Bracket** (Providing a robust mounting platform for angle adjustments on a 3-axis plane.)

Video Content Analysis

Milesight VCA with 8 detection modes provides advanced, accurate smart video analysis for Milesight network cameras, enabling the comprehensive surveillance function and quicker response to different monitoring scenes.



0.002Lux Ultra Low-light

The starlight camera is able to deliver high detailed color images even in low light environment reaching 0.002Lux(Color) or 0Lux(B/W), and near infrared light environments without any supplementary lighting.

140dB Super WDR

Milesight's sensor-based WDR technology allows the camera to record greater scene details with true color reproduction even under the extreme back light and high contrast conditions. The ratio that the brightest light signal values divided by the darkest light signal values is up to 140dB.



Weather-proof Design

For easy management and weather resistant, the camera is also equipped with a mounting bracket that conceals the cable within, offering a well-rounded protection of the cable from any water, dust or shock damages.

H.265 Remote Focus&Zoom Mini Bullet Network Camera




	Model	MS-C2963-F(I)PB (2MP)	MS-C3763-F(I)PB (3MP)	MS-C4463-F(I)PB (4MP)	MS-C5363-F(I)PB (5MP)	
Camera	Image Sensor	1/2.8" Progressive Scan CMOS		1/3" Progressive Scan CMOS	1/2.9" Progressive Scan CMOS	
	Min. Illumination	Color: 0.002Lux@F1.2 B/W: 0Lux with IR on	Color: 0.005Lux@F1.2 B/W: 0Lux with IR on	Color: 0.008Lux@F1.2 B/W: 0Lux with IR on	Color: 0.006Lux@F1.2 B/W: 0Lux with IR on	
	WDR	Super WDR up to 140dB		Super WDR up to 120dB		
	Lens	Motorized 2.8~12mm @F1.4 P-Iris(Optional)				
	Mount	Φ14				
	Field of View	H83.1°~H33.7°/ D96.1°~D38.7°/ V45.9°~V19°	H74.5°~H30.7°/ D93.8°~D38.3°/ V55.6°~V23.1°	H77.4°~H31.5°/ D90.3°~D36.4°/ V44.7°~V18.5°	H67.9°~H30.4°/ D84.1°~D36.7°/ V51.9°~V24°	
	Shutter Time	1/100000s~1/5s				
	IR Distance	Up to 45m				
	Day&Night	ICR Filter Auto Switch				
Video	Max. Image Resolution	1920×1080	2048x1536	2592×1520	2560×1920	
	Primary Stream	30fps@(1920×1080, 1280×960, 1280×720, 704x576)	30fps@(2048x1536, 1920×1080, 1280×960, 1280×720, 704x576)	20fps@(2592×1520), 30fps@(2304x1296, 1920×1080, 1280×960, 1280×720, 704x576)	20fps@(2560×1920, 2592×1520), 30fps@(2304x1296, 1920×1080, 1280×960, 1280×720, 704x576) 30fps@2560×1920(Optional)	
	Secondary Stream	30fps@(704x576, 640×480, 640×360, 352x288, 320x240, 320x192, 320x176)				
	Tertiary Stream	30fps@(1920×1080, 1280×720, 704×576, 640×480, 640×360, 320×240, 320x192, 320x176)				
	Video Compression	H.265 ⁺ /H.265(HEVC)/H.264 ⁺ /H.264/MJPEG				
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)				
	Image Setting	Brightness/Contrast/Saturation/Sharpness				
Network	Ethernet	1*RJ45 10M/100M Ethernet Port				
	Network Storage	NAS(Support NFS, SMB/CIFS)				
	Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, PPPoE, VLAN, 802.1x				
	Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 128G				
	Advanced Function	Motion Detection, Privacy Masking, Backlight Compensation, HLC, 3D-DNR, ROI, Anti-fog				
	SIP/VoIP Support	Yes, Voice & Video-over-IP				
	Event Trigger	Motion Detection, Network Disconnection, etc.				
	Event Action	FTP Upload/ SMTP Upload/ SD Card Record/ SIP Phone				
	Video Analysis (Optional)	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting				
System Compatibility	ONVIF Profile S					
General	Working Temperature	-30℃~60℃				
	Working Humidity	0~90%(Non-condensing)				
	Power Supply	PoE/ DC 12V±10%				
	Power Consumption	5.5W MAX 9.5W MAX (With IR on)	6W MAX 9.5W MAX (With IR on)	4.5W MAX 7W MAX (With IR on)		
	Weather Proof	Up to IP67-rated for Weather-resistant Performance				
	Weight	820g				
	Dimensions	Φ76mmX236mm				
	Warranty	3/5 Years				

H.265 Remote Focus&Zoom Mini Bullet Network Camera



Structure Diagrams



Units: mm

Accessories Support

A01 Pole mount with stainless steel straps
Weight: 720g
Dimensions: 170*51.5*152.6mm



A01-N Pole mount with stainless steel straps
Weight: 730g
Dimensions: 170*51.5*152.6mm



A02 Corner bracket
Weight: 540g
Dimensions: 170*23.2*205.3mm



A03 Corner bracket
Weight: 900g
Dimensions: 170*152.6*76.3mm



A63 Junction Box
Weight: 620g
Dimensions: 134*127*40



Naming Convention



Milesight Technology Co.,Ltd. | www.milesight.com



Add: 7509 N.W. 36th Street, Miami, Florida 33166, USA
Tel: +1-800-561-0485
Mail: sales@milesightusa.com

Add: 9F/901, Star Valley B/D Digital-ro 9gil 99, Geumcheon-gu, Seoul, Korea
Tel: +82-2-839-3335
Mail: charley@milesight.co.kr

Add: No.23 Wanghai Road, 2nd Software Park, Xiamen, China
Tel: +86-592-5922772
Mail: sales@milesight.com

