Akuvox A02 Datasheet

Perfect choice for Access Control

Akuvox's A02 is an access control terminal that incorporates a RFID reader and touch keypad. It supports multiple modes of door access authentication for the users (PIN code, NFC and RFID). And it can be easily connected to a POE using an Ethernet cable for data transmission. A02 provides you with greater security and flexibility than those traditional access control systems.

1 2 3 4 5 6 7 8 9 * 0 ✓

At a Glance

- Stylish appearance design;
- 20,000 card capacity & 50,000 Event Log;
- Multi-frequency RFID card reader;
- Cardless access control via NFC;
- Two-factor authentication;
- Compatible with Akuvox cloud;
- Configuration via web browser;
- Management access authority via ACMS(Access Control Management System);

Physical & Power

- Front panel: Toughened Glass
- Frame: Aluminum
- RF card reader: 13.56MHz & 125kHz
- Touch Keypad
- Relay out: 1
- Inputs: 2
- Speaker: 8Ω / 0.5W
- Tamper: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet

- 12V DC connector (if not using PoE)
- IP Level: IP65
- Installation: Flush-mounted or Wall-mounted
- Flush-mounted DIM: 86x86x16mm
- Wall-mounted DIM: 86x86x27mm
- Working Humidity: 10~90%, no condensing
- Working Temperature: -20°C ~ +55°C
- Storage Temperature: -30°C ~ +70°C