Akuvox E12S Datasheet

## Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone E12S alerts you when the bell is rung and lets you see and speak with visitors from your smartphone, from anywhere.

## At a Glance

- Real-time 2-way audio;
- Live camera viewing;
- Cloud or local based storage;
- Rated for outdoor use;
- Mobile App compatible;
- Integrated with any SIP device;

## Physical & Power

- Body Material: Plastic
- Camera: 2M pixels, automatic lighting
- Button: 1 call button with backlight
- Wiegand port: Support
- RF card reader: 13.56MHz
- Light sensor: 1
- Relays out: 1
- Inputs: 2
- Micro SD card slot: 1
- Microphone: -36dB
- Speaker: 8Ω / 15W



- Ethernet port: RJ45, 10/100Mbps adaptive
- BLE: Yes
- Vandal alarm: Yes
- 802.3af Power-over-Ethernet
- 12V DC connector (if not using PoE)
- Water-proof & Dust-proof: IP65
- Installation: Wall-mounted
- Size: 146x70x23mm
- Working Humidity: 10~90%
- Working Temperature: -20°C ~ +55°C
- Storage Temperature: -40°C ~ +70°C

